

Xerox® EC8036*/EC8056 Color Multifunction Printer

Convenience Stapler (Includes Work Surface. Available while supplies last)



Envelope Tray (replaces Tray 1, optional and available while supplies last)



Office Finisher LX (optional). Shown with Booklet Maker (optional, available while supplies last)

Xerox[®] EC8000 Series Color Multifunction Printers are built on Xerox[®] ConnectKey[®] Technology. For more information, go to www.ConnectKey.com.

SYSTEM SPECIFICATION	EC8036*	EC8056	
Speed			
Color/Black-and-White	Up to 35/35 ppm	Up to 50/55 ppm	
Monthly Duty Cycle ¹	Up to 110,000 pages/month	Up to 300,000 pages/month	
Recommended Average Monthly Print Volume ²	5,000 to 15,000 pages	8,000 to 22,000 pages	
Hard Drive/ Processor/Memory	Minimum 250 GB HDD/Intel® Atom™ Quad Core 1.91 GHz/2 MB Cache/8 GB system memory		
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, Wi-Fi Direct with optional Xerox® USB Wireless Adapter, Near Field Communication (NFC)		
Controller Features	Unified Address Book, Remote Control Panel, Configuration Cloning, Online Support		
COPY AND PRINT			
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 2400 dpi		
First-Print-Out Time Color/Black-and-white	As fast as 6.4/5.2 seconds	As fast as 6.0/4.7 seconds	
First-Copy-Out Time (from platen/warmed up state)	As fast as 8.1 seconds/As fast as 6.7 seconds	As fast as 7.2 seconds/As fast as 5.7 seconds	
Page Description Language	Adobe® PostScript®3™, Adobe® PDF, PCL® 5c/PCL 6		
Print Features	Print from USB, Encrypted Secure Print, Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs		
MOBILE-AND CLOUD-READY			
Mobile Printing	Xerox® @PrintByXerox App, See more at xerox.com/MobileSolutions; Optional: Xerox® Workplace Cloud/Suite Mobile Print Solution. Learn more at xerox.com/MobilePrintApp		
Mobile Connectivity	Apple® AirPrint®, Xerox® Print Service Plug-in for Android™, Mopria® Print Service Plug-in for Android, NFC, Wi-Fi Direct Printing, Xerox® Print Service Plug-in for Android™		

Detailed Specifications Page 1 of 11

MOBILE-AND CLOUD-R	EADY		
Mobile Apps and	_	, eSign, personalize print, convert, route, collaborate and communicate.	
Xerox App Gallery	Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)		
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional : Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their printer fleet while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by		
SCAN			
Standard Features	Destinations: Scan to USB/Email/Network (FTP/SMB); File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan to Home Searchable PDF, Single/Multi-Page PDF/TIFF, Password Protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support		
Optional Features	ConnectKey® for DocuShare®, other solutions available through various Xerox Business Innovation Partners at www.office.xerox.com/Software-Solutions		
FAX			
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement		
Optional Features	Fax Forward to Email or SMB Share, Walk-up Fax (one-line opti	on,includes LAN Fax)	
SECURITY			
Standard Features	McAfee® ePolicy Orchestrator Integration, HDD Overwrite, AES 256-bit Encryption (FIPS 140-2 compliant), SSL, SHA-256 Hash Message Authentication, Common Criteria Certification (ISO 15408)², Encrypted Secure Print, Secure Fax, Secure Scan, Configuration Watchdog, Fleet Orchestrator, Secure Email, Network Authentication, TLS, SNMPv3, Audit Log, Access Controls, User Permissions, Cisco® Identity Services Engine (ISE) compatible		
Optional Features	McAfee® Integrity Control, Smart Card Enablement Kit (CAC/P	IV/.NET), Xerox® Integrated RFID Card Reader	
ACCOUNTING			
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Ne	etwork Accounting Enablement	
Optional Features	Equitrac®, YSoft® Papercut®, other network accounting solution	ns available through various Xerox Business Innovation Partners	
DEVICE SPECIFICATIO	N		
Control Panel Languages	US English, International French		
Accessories			
Optional	Envelope Tray (Replaces Tray 1)³ Convenience Stapler (includes Work Surface)³ Office Finisher LX (optional with EC8036, EC8056) Booklet Maker for Office Finisher LX³ Hole Punch for Office Finisher LX Smart Card Enablement Kit Walk Up Fax (One-line, includes LAN) Wi-Fi Direct with Optional Xerox® USB Wireless Adapter McAfee® Integrity Control Enablement Kit Keyboard Kit (Wired/USB) Xerox® Integrated RFID Card Reader		
Xerox® Foreign Device Interface (FDI)	Also known as Auxiliary Access Device, this is an interface to third-party access control devices, such as coin machines and card readers		
Electrical Requirements	EC8036*	EC8056	
North America	Voltage: 110-127 VAC +/- 10 % Frequency: 50/60 Hz +/- 3 %, 15 A		
Power Consumption	EC8036*	EC8056	
Running (Average)	115V: 687 watts	115V: 787 watts	
Standby Mode	115V: 64 watts	115V: 95 watts	
Auto Off/Sleep Mode	115V: 1.2 watts	115V: 1.2 watts	
Warm-up (from Off)	As fast as 100 seconds		
Recovery from Low Power	As fast as 2 seconds		
Recovery from Sleep	As fast as 6.2 seconds		

Detailed Specifications Page 2 of 11

Operating Environment			
Required Temperature Range	50 to 82° F/10 to 28° C		
Required Relative Humidity	15% to 85%		
Sound Power Levels	Operating: 63.9 dB(A) Standby: 3.32 dB(A)	Operating: 68.3 dB(A) Standby: 3.35 dB(A)	
Dimensions and Weight			
Base Configuration	Width: 25.2 in./640 mm Depth: 28.9 in./723.8 mm Height: 45 in./1,142.7 mm Weight: 321 lb./151.9 kg		
With Office Finisher LX (with Booklet Maker)	Width: 46.5 in./1,182 mm Depth: 28.9 in./732.8 mm Height: 45 in./1,142.7 mm Weight: 390 lb./177.2 kg		
System Certification/Regulator	ry Compliance		
Certifications	To view the latest list of certifications, go to www.xerox.c	om/OfficeCertifications	
PAPER HANDLING	EC8036*	EC8056	
Single-pass Duplex Automatic	Document Feeder (DADF)		
Capacity ⁴	130 sheets		
Speed	Up to 80 pages per minute Black-and-White and Color (simplex) Up to 139 images per minute (ipm) Black-and-White and Color (duplex)		
Paper Sizes Sensed	3.4 x 4.9 in. to 11.7 x 17 in./85 x 125 mm to 297 x 431.8 i	mm	
Weights	16 lb. to 32 lb. bond/60 to 128 gsm		
Bypass Tray			
Capacity ⁴	100 sheets		
Sizes	Custom Sizes: 3.5 x 3.9 in. to 12.6 x 19 in./89 x 98 mm to	320 x 483 mm	
Weights	16 lb. bond to 110 lb. cover/60 to 300 gsm		
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Glossy Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Lightweight Card Stock Reloaded Hole Punched Labels Letterhead Lightweight Card Stock Reloaded Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies		
Trays 1 and 2 (Standard)			
Capacity ⁴	520 sheets each		
Sizes	Tray 1: Custom Sizes: 5.5 x 7.2 in. to 11.7 x 17 in./140 x 182 mm to 297 x 432 mm short edge feed (SEF) Tray 2: Custom Sizes: 5.5 x 7.2 in. to 12 x 18 in./140 x 182 mm to SRA3 (SEF)		
Weights	16 lb. bond to 140 lb. index/60 to 256 gsm		

Detailed Specifications Page 3 of 11

Media Types	Bond		
	Card Stock Card Stock Reloaded		
	Cara Stock Reloaded Custom		
	Envelopes		
	Glossy Card Stock		
	Glossy Card Stock Reloaded		
	Heavyweight Card Stock		
	Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock		
	Heavyweight Glossy Card Stock Reloaded		
	Hole Punched		
	Labels		
	Letterhead		
	Lightweight		
	Lightweight Cardstock Lightweight Card Stock Reloaded		
	Lightweight Glossy Card Stock		
	Lightweight Glossy Card Stock Reloaded		
	Plain		
	Plain-Reloaded Provinted		
	Preprinted Recycled		
	Transparencies		
High Capacity Tandem Tray			
Capacity ⁴	Tray 3: 867 sheets		
Cupacity	Tray 4: 1,133 sheets		
Sizes	8.5 x 11 in./A4, JIS B5, Executive (7.25 x 10.5 in) LEF		
Weights	16 lb. bond to 140 lb. index/60 to 256 gsm		
Media Types	Bond		
	Card Stock		
	Custom Glossy Card Stock		
	Hole Punched		
	Labels		
	Letterhead		
	Lightweight Cardstock		
	Lightweight Glossy Card Stock Plain		
	Preprinted		
Envelope Tray (Optional - Re			
Capacity ⁴	Up to 60 envelopes		
Sizes	#10 Commercial (9.25 x 4.125 in.)/Monarch, DL, C5		
3.233	Custom Sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm		
Weights	20 lb. to 24 lb. bond/75 to 90 gsm		
Total Capacity			
Device Total Capacity ⁴	High Capacity Tandem Tray Module: 3,140 sheets		
FINISHING	EC8036* EC8056		
Output Trays (Standard) (Du	ıal Offset Catch Trays limited to one with LX Finishers)		
Stacking Tray Capacity ⁴	Dual Offset Catch Tray: Up to 250 sheets each		
	Left Side Face up Tray: Up to 100 sheets		
Office Finisher LX (Optional)			
Stacking Tray Capacity ⁴	2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4)		
Stacking Tray Sizes	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm		
Weights	16 lb. bond to 80 lb. cover/60 to 256 gsm		
Multiposition Stapling	50 sheets of 24 lb. bond/90 gsm		
Hole Punch (Optional)			
North America	2-3-hole punch		
Europe	2-4-hole punch		

Detailed Specifications Page 4 of 11

Xerox® EC8036*/EC8056 Color Multifunction Printer

Booklet Maker for Office Fin	isher LX (Score/Crease, Saddle-stitch Staple) (Optional) ³		
Top Tray Capacity⁴	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)		
Sizes	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Ledger – 11 x 17 in./A3 SEF		
Saddle-Stitch Stapling	2-15 sheets/8-60 page booklet 16 lb. to 24 lb. bond/60 x 90 gsm		
Score/Crease	1-15 sheets/unstapled		
Convenience Stapler (Option	nal - Includes Work Surface)³		
Capacity⁴	50-sheet stapling 5,000 staples Requires separate power outlet		
COPY	EC8036*	EC8056	
First-Copy-Out Time (from platen/warmed up Color/Black-and-White)	As fast as 8.1 seconds/As fast as 6.7 seconds	As fast as 7.2 seconds/As fast as 5.7 seconds	
Sides (input:output)	1-1, 1-2, 2-2, 2-1		
Quantity	1 to 9,999		
Resolution (max)	Up to 600 x 600 dpi		
Reduction/Enlargement	Variable zoom from 25% to 400% in 1% increments		
Concurrency	Program-ahead to allow the job to be initiated while the initial job i	s processed (Copy, Print, Fax, and Scan)	
Copy Features	Program-ahead to allow the job to be initiated while the initial job is processed (Copy, Print, Fax, and Scan) Annotation and Bates™ stamping (with color capability and font size adjustment) Authentication for Services (i.e., Color Copy) Auto Paper Select Auto Reduction and Enlargement (To fit selected paper size) Auto Tray Switching Automatic 2-sided/Duplex Booklet Creation Build Job (Enables page-level programming and also lets you proof each section or delete the last section as the job is built) Collation Covers (Front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Center option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Color Stapling Transparencies		

Detailed Specifications Page 5 of 11

PRINT	EC8036* EC8056		
Resolution	Up to 1200 x 2400 dpi		
Print Features	ation Defaults er Sheet Enable/Disable m Color Options (Color By Words) Bi-directional Real-time Status Selection Print (specific time) User Permissions e Options (Toner Saver, Resolution (Standard, Enhanced, High) lentification (Print ID or Banner, Print ID in margins on the first page only or all pages) ax (requires optional Fax Kit) t/Watermark lup to 16 pages per sheet) et Layout ing New Paper Size All Jobs Selection by Attribute Sample Set Job (color jobs can be printed as monochrome) e Print with Timed Deletion all Pages (exception page programming: covers, inserts, exception pages) and Recall Driver Settings nability Features (Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) ided Printing (as default)		
Print from USB	Allows walk-up printing from Type A USB port on the front panel Supports direct printing from the computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL Color jobs can be printed as black-and-white		
Operating Systems	Windows Server 2008 SP2 (32- and 64-bit) Windows Server 2012 and R2 (64-bit) Windows Server 2012 and R2 (64-bit) Windows Server 2016 (64-bit) Windows Server 2019 (64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.13, 10.14, 10.15 Fedora® Core Ubuntu®		
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Bonjour®/AirPrint® IPv6 Secure FTP Most protocols not in use can be disabled		
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS		
Font Capability	PCL: 93 scalable fonts, line printer, and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts		
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management		
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Xerox® Virtual Print Management Service and others		
UNIFIED ADDRESS BO	OK FOR FAX, INTERNET FAX, EMAIL, AND SCAN TO		
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favorites for quick access of all services supported		

Detailed Specifications Page 6 of 11

SCAN	EC8036* EC8056		
Concurrency	Scan while the system is printing, copying, or while it is transferring scan to network or fax jobs (priority is for return of scanned originals and printing concurrent jobs)		
Input Speed	Up to 80 page per minute Black-and-White and Color (simplex) Up to 139 images per minute (ipm) Black-and-White and Color (duplex)		
Resolution	72 x 72 dpi to 600 x 600 dpi		
Bit Depth	1-bit (Black-and-White), 8-bit (Grayscale), 24-bit (Color)		
Maximum Scan Area	11 x 17 in./A3		
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® Internet Services scan templates and share via device cloning to other Multifunction Printers' confirmation sheet options		
Network Protocols	sFTP, FTP, SMB, HTTP, HTTPS		
File Compression	Color TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-White TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for Black-and-White and within MRC)) Linearized PDF/PDF/A		
Document Management Fields (Metadata)	Features only available in Network Scan to File Templates: • 1 to 6 user-programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value, and other configurations • Customized fields viewed on user interface for variable data input		
Scan Features	Mixed Size Originals Scan Build Job Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper/Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support/WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)		
Scan to Email (Standard)			
Scan Features	 Email signatures (6 lines each of 128 character max), email message body (user-configurable), email CentreWare® Internet Services confirmation sheet options Scan to Email S/MIME Encryption Email signing (requires Smart Card option) Auto send to self 		
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino) Device Address Book		
Scan to (Standard)			
Features	Scan to USB Scan to Network Folder (uses Unified Address Book entries) Scan to Home Scan to Network Scan to Email Scan to PC/Server Client (SMB or FTP) Scan to Mailbox Scan to Secure FTP and HTTPS		
Workflow Scanning (Option	al)		
Scanning Software	Autostore v7 ecopy ShareScan v5.2 e Copy ScanStation v5.2		
Scanning Apps and Xerox App Gallery	Scan to/from: Google Drive [™] , Microsoft [®] OneDrive [®] , Microsoft Office 365 [™] , and Box [®] Xerox [®] Workplace Mobile App (iOS/Android) See the full list of apps available in the Xerox App Gallery: www.xerox.com/AppGallery		

Detailed Specifications Page 7 of 11

SECURITY	EC8036* EC8056	
Features	Expanded Authentication	
Xerox® Integrated RFID	Expanded Authorization Saccess based on network credentials Authorization per service User Permissions required to access Print and Print Features (e.g., color access, or time restrictions) reflects in the print driver Scaure Nathorization per service User Permissions required to access Print and Print Features (e.g., color access, or time restrictions) reflects in the print from USB Enable/Disable Print from USB Enable/Disable Immediate Disable Print from USB Enable/Disable Immediate Image Overwrite (Scheduled) Reacurity settings): Scare Pint (up to 10 digit PlN or network authentication) Immediate Image Overwrite (Scheduled, Manual) includes sanitation of unused area of the disk FIPS 140-2 256 bit Hard Disk Encryption, TLS, IPPS, HTTPS, SFTP, SNMPv3 Expanded Authorization SA access based on network credentials Authorization per user per service User Permissions required to access Print and Print Features (e.g., color access, or time restrictions) reflects in the print driver Scaure Network Access Configuration Watchdog (Monitor and remediate 8 security settings): Scan to USB Enable/Disable Print from USB Enable/Disable Front USB Port Enable/Disable Immediate Job Overwrite Enable/Disable McAfee® Embedded Control Enable/Disable Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPs, 802.1X, SFTP McAfee® Embedded Control Enable/Disable Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPs, 802.1X, SFTP McAfee® Embedded Control Enable/Disable Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPs, 802.1X, SFTP Integrated support for most industry security cards providing additional security, with embedded multifunction printer card readers in	
Card Reader E1.0 (Optional kit)	the multifunction printer panel	
FAX	EC8036* EC8056	
Network Server Fax Features	S	
Compatibility	ITU (CCITT) group 3; Various Xerox Business Innovation Partner Solutions	
Maximum Scan Area	11 x 17 in./A3	
Fax Send Features	One-or Two-sided Scanning (up to 11 x 17 in./A3) Add to Send List (200 numbers maximum) Build Job, Favorites, Delay Send (specific time) Original Type (photo, text or photo and text)	
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print	
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi	
Internet Fax Features		
Compatibility	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients	
Directory Access	Utilizes the Unified Address Book	
Send/Receive	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG	
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (Black-and-White)	
Network Protocols	SMTP (send), POP3 (receive)	
Compliance	ITU-T T.37 compliant	

Detailed Specifications Page 8 of 11

Walk-up Fax Features (Custo	mer-installable – 1 line)		
Compatibility	ITU (CCITT) Group 3		
Speed/Modems	One V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time		
Compression/Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3		
Resolution	Walkup Send:		
Resolution	Standard: 200 x 100 dpi		
	Fine: 200 x 200 dpi Superfine: 600 x 600 dpi		
	Receive: Accepts all sizes		
Fax Send Features	LAN Fax (fax from the print driver)		
	Auto Fax Transmission Reduction		
	Page-by-page Job Status at the Machine Delay Start, Build Job, Favorites		
	Automatic Memory Resend		
	Automatic Cover Sheets		
	PSTN Fax		
	Batch Send (up to memory capacity)		
	Device Address Book (up to 5,000 contacts)		
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled		
	Receive Print Mode – Manual (size, margin, stock, header)/Auto		
	Output Tray Selection		
	Up to 200 Password Protected Mailboxes		
	Secure Receive		
	Receive Timestamp		
	Auto Answer Delay		
Fax Forward	Forward to Email or SMB Location		
F D .	Fax Forward on Receive Only		
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report		
Director: Acces			
Directory Access Utilizes the Unified Address Book Group fax available			
Auto Redial	Up to 14 attempts (per country requirements)		
Auto Rediai	1 to 25-minute intervals		
Auto Resend	Up to 5 attempts		
DEVICE MANAGEMENT			
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP		
Wanagement Support	MIB access (IETF-MIBII RFC 1213)		
	Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Fleet Orchestrator, Configuration Watchdog		
Xerox® CentreWare® Web	A Web-based server application for network administrators that permits Web browser-based device management from any workstation,		
	whether running Windows, UNIX, or any other operating system:		
	Works with any SNMP-managed printer from any manufacturer		
	Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management		
	Requires Windows 7 and Internet Explorer 6.0 and higher		
	Auto-detect Xerox® CentreWare® Web application and download configurations files for touchless remote installation		
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management		
ACION Device Muliugei	environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally		
	connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides:		
	Device monitoring and troubleshooting		
	Extensive reporting and discovery of new devices		
	Usage collection, chargeback, and billing capabilities		
	Auto-detect Xerox® Device Manager server and download configurations files for touchless remote installation		
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer		
	connection. The following data can be shared: Software update files, clone files, and 1-Touch App files		

Detailed Specifications Page 9 of 11

Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. www.office.xerox.com/Software-Solutions	
Device Types for SAP R/3 Intelligent Barcode Utility (optional)	des built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific ons of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript are Types for SAP environment and Xerox® Font Center Barcode Fonts. Information is available at: www.office.xerox.com/Software-Solutions	
Xerox® Embedded Web Serv	er — Integrated Device Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: Tray status/contents Consumables status Alerts Remote Control Panel	
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)	
Device Administration	Allows simple, remote installation setting of configuration options and management of the device	
Xerox® Embedded Web Serv	er — Integrated Device Web Pages Provided by the Device	
Browsers	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x through 53.x Opera 25.x through 53.x Chrome 48.x through 72.x	
Support	Install print/scan drivers and online support available via support.xerox.com	
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic	
Remote Services		
Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time	
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® Output Devices based on actual usage, eliminating the need to manually manage supplies inventory	
ACCOUNTING		
Xerox® Standard Accounting	Feature	
Tracking	Copy, Print, Fax, Scan, and Email usage	
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group accounts (Department)	
Features	 Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry-standard CSV file 	
Accounting Options – Netwo	rk Accounting (Allows central server to manage all accounting)	
	 Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan, and server fax Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at the control panel and pass to third-party Networking Account Interface with third-party accounting terminal 	

Detailed Specifications Page 10 of 11

Xerox® EC8036*/EC8056 Color Multifunction Printer

SUPPLIES	DESCRIPTION	QUANTITY	PART NUMBER
Supplies			
Toner Cartridge (Metered) ⁵	Black Cyan Magenta Yellow	26,000 pages 15,000 pages 15,000 pages 15,000 pages	006R01509 006R01512 006R01511 006R01510
Toner Cartridge (Sold) ⁵	Black Cyan Magenta Yellow	26,000 pages 15,000 pages 15,000 pages 15,000 pages	006R01697 006R01698 006R01699 006R01700
Transfer Belt Cleaner	1 Assembly	160,000 pages	001R00613
Second Bias Transfer Roll	1 Assembly	200,000 pages	008R13064
Staple Cartridges	Office Finisher LX and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	For Office Finisher LX Booklet Maker (8 cartridges per carton)	2,000 each cartridge	008R12897
Staple Refills	Office Finisher LX, and Convenience Stapler (3 refills per carton)	5,000 each refill	008R12941
Xerox® Smart Kit® Techi	nology		
Drum Cartridge ⁶	1 Cartridge per Color	125,000	013R00662
Waste Toner Container with Suction Filter ⁷	1 Cartridge	43,000	008R13061

^{*} Xerox® EC8036 model not available in all sales channels.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.



¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Common Criteria Certification expected post launch.

 $^{^{\}rm 3}$ Available while supplies last.

⁴ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.
⁵ Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in./A4 LEF. Toner yield can vary due to many factors, including but not limited to the image area coverage, image content, media size, run mode, application types, monthly print volumes, and image quality set-points.

⁶ Average drum yield is based on a run length of 5 pages of 8.5 x 11 in./A4 LEF pages, with split of 30% color/70% black-and-white pages.

⁷ Waste Toner Container yield will vary depending on the type of image, area coverage %, and Job run length.