

Xerox[®] VersaLink[®] B400 Printer

VersaLink[®] B400 Printers are built on Xerox[®] ConnectKey[®] Technology. For more information, go to www.ConnectKey.com.



SYSTEM SPECIFICATIONS	VERSALINK [®] B400	
One-sided Speed¹ 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 47 ppm black-and-white Up to 45 ppm black-and-white Up to 38 ppm black-and-white	
Two-sided Speed¹ 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 29 ppm black-and-white Up to 28 ppm black-and-white Up to 25 ppm black-and-white	
Monthly Duty Cycle ²	Up to 150,000 pages / month	
Recommended Average Monthly Print Volume ³	Up to 15,000 pages	
Processor	1.05 GHz Dual Core	
Memory	2 GB	
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair	
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform [®] , Xerox [®] App Gallery App, Xerox [®] Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support	
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian	

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127 VAC Frequency: 50/60 Hz 11 A			
Europe and Other Geographies	Voltage: 220-240 VAC Frequency: 50/60 Hz 6 A			
POWER CONSUMPTION	L			
Continuous Printing ⁴	565 watts or less			
Ready (Standby) ⁴	46 watts or less			
Energy Saver (Sleep Mode) ⁴	4 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32 to 95° F / 0 to 35° C			
Required Temperature Range (Operating)	50 to 90° F / 10 to 32° C			
Required Relative Humidity	10% to 85%			
Sound Power Levels Operating Standby	7.5 B(A) or less 5.3 B(A) or less			
Sound Pressure Levels Operating Standby	56 dB(a) or less 30 dB(a) or less			
Boot Time (from Off to UI Ready)	As fast as 60 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 5 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® B400	18.1 in. / 459 mm	16.8 in. / 426 mm	13.3 in. / 339 m	nm 30 lb. / 14 kg
550-sheet Paper Tray	15.5 in. / 393 mm	15.5 in. / 393 mm	3.7 in. / 94 mm	7 lb. / 3.2 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® B400	21.3 in. / 540 mm	23.1 in. / 588 mm	21.7 in. / 480 m	nm 38.3 lb. / 17.35 kg
550-sheet Paper Tray	19.6 in. / 498 mm	19.8 in. / 504 mm	9.2 in. / 234 mr	m 9.6 lb. / 4.4 kg
SYSTEM CERTIFICATION/REGUL	ATORY COMPLIANCE			
Certifications	To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.			
PRINT				
First-Print-Out Time	As fast as 4.7 seconds			
Print Resolution	Up to 1200 x 1200 dpi (enhanced)			
Page Description Languages	PCL [®] 5e, 6 PDF XPS	TIFF JPEG		HP-GL Adobe [®] PostScript [®] 3™
Maximum Print Area	4 mm from edge of paper			
	4 min nom euge of pupe	1		

	Banner Pages Enable / DisableBi-directional Real-time StatusBooklet LayoutDraft ModeFit to New Paper SizeJob Identification (Print ID or Banner, Print ID in margins on first page only or all pages)Job Monitoring (Client or Local User Interface)N-up Page Layout (up to 16 pages per sheet)Paper Selection by AttributePersonal PrintPrint Around Enable / DisablePrint from USBSample SetSaved JobScalingSecure PrintSkip Blank PagesSpecial Pages (exception page programming: covers, inserts, exceptions pages)Store and Recall Driver SettingsStored Jobs DeletionTwo-sided PrintingWatermark (predefined and custom)Xerox® Earth Smart Driver Settings	
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A	
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com	
Fonts	PostScript fonts: 136 PCL fonts: 83	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.	
Xerox [®] Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.	

Xerox [®] ConnectKey Apps	nd at the Xerox App ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download		
(Found at the Xerox App Gallery)			
MOBILE SOLUTIONS AND MOBII	E DEVICE APPS		
Apple [®] AirPrint [®]	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.		
Mopria® Certified	ConnectKey Technology-enabled MFPs are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.		
Xerox [®] @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android [™] , Google [®] Chromebook [™] and more) to a Xerox [®] printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.		
Xerox [®] Print Services plug-in for Android™ (Free at Google Play™ Store)			
Xerox [®] Workplace Suite and Xerox [®] Workplace Cloud	Xerox [®] Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud-based version (Workplace Cloud) of this solution.		
SECURITY			
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL Trusted Platform Module (TPM)		

ACCOUNTING				
	COUNTING TOOL/NETWORK ACC	OUNTING (STANDARD)		
Tracking Accounting	Print usage Xerox® Standard Accounting Tool Up to 1,000 User Accounts without SSD Up to 9,999 User Accounts with SSD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without SSD Up to 60,000 User IDs; Up to 60,000 Account IDs with SSD Up to 14,000 Accounting Records (transactions)			
Features	Administrator can mana	ge the feature via the Embedded We	b Server.	
ACCOUNTING OPTIONS		OWS CENTRAL SERVER TO MANAG		
	 Comprehensive mana Numerous solutions a Security enhancemen Device requests accou accounts Accept Authentication 	ts include simultaneous support for H ⁻	and reporting of print usage rtners. For details visit www.xerox.com TTP/HTTPS protocols rver enabling larger databases of users and hird party Networking Account	
PAPER HANDLING				
BYPASS TRAY				
Capacity ⁵	150 sheets	150 sheets		
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 356 mm			
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 60 lb. cover / 60 to 163 gsm			
Media Types	Bond Plain Paper Cardstock Custom	Envelopes Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled	
TRAY 1				
Capacity ⁵	550 sheets			
Sizes	Custom Sizes: 3 x 5 in. to 8.5 x 14 in. / 76.2 x 127 mm to 216 x 356 mm			
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 60 lb. cover / 60 to 163 gsm			
Media Types	Bond Plain Paper Cardstock Custom	Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled	
OPTIONAL TRAY 2				
Capacity ⁵	550 sheets	550 sheets		
Sizes	Custom sizes: 5.5 x 8.3 in. to 8.5 x 14 in. / 139.7 x 210 mm to 216 x 356 mm			

Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 60 lb. cover / 60 to 163 gsm		
Media Types	Bond Plain Paper Cardstock Custom	Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled
TOTAL CAPACITY ⁵			
Device Standard Capacity ⁵	700 sheets		
Device Total Capacity ⁵	2,350 sheets		
PAPER OUTPUT			
Output Capacity ⁵	250 sheets		
Automatic Two-sided Printing	Standard		
DEVICE MANAGEMENT			
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint® Most protocols not in use can be disabled		
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS		
REMOTE CONTROL PANEL			
	• IT administrators an	convenient technical support and user d authorized users can control the devi nce is identical to performing tasks dire	ce remotely from a web page on anydevice
XEROX [®] CENTREWARE [®] WEB	- H		
EMBEDDED WEB SERVER – INTI	 A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system Works with any SNMP-managed printer from any manufacturer Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management 		
Device Status	 Tray Status / Contents Consumables Status Billing / Usage Quick Links Online Support 		
Print Queue Viewing	Job print queue management — view and delete		
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device		
Browsers	Microsoft [®] Internet Explorer [®] Microsoft Edge [™] Mozilla [™] Firefox [®] Apple [®] Safari [®] Google Chrome [™]		

REMOTE SERVICES			
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox [®] device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.		
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.		
WHAT COMES IN THE BOX			
	VersaLink® B400 Printer Standard Capacity Toner Cartridge: 5,900 print capacity ⁶ Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord		
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER	
SUPPLIES			
Standard Capacity Toner Cartridges	5,900 standard pages ⁶	106R03580	
High Capacity Toner Cartridges	13,900 standard pages ⁶	106R03582	
Extra-High Capacity Toner Cartridges	24,600 standard pages ⁶	106R03584	
Drum Cartridge	65,000 standard pages ⁷	101R00554	
ACCESSORIES / OPTIONS			
550-sheet Paper Tray		497K13620	
Productivity Kit with 16 GB Solid State Drive		097504913	
Stand		497K13660	
Wireless Network Adapter Kit		497K16750	
External Card Reader / RFID Kit		497K18380	

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR[®] Program requirements for Imaging Equipment.
 ⁵ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.
 ⁶ Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

⁷Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: https://www.office.xerox.com/Latest/SUPGL-01.pdf.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.

©2020 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, ConnectKey®, Global Print Drive®, Mobile Express Driver® and VersaLink® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 02/21 TSK-1426 BR26410 VB4SS-01UH

